

Article number: 03 998 03 99

Frost-resistant outdoor tap POLAR II set

Kit for conduit installation during preliminary building work. Frost-safe valve seat in masonry for wall thicknesses of 200-500 mm.



Scope of delivery

- Frost-resistant outdoor tap
 - Conduit with integrated valve seat
 - Fitting housing with lockable head part and COMFORT operating handle
 - Backflow preventer
 - Anti-vacuum device
 - Long valve shaft
- Hose screw connection
- Protective pipe
- Installation plug
- Cut-to-length gauges
- Anti-twist wall rosette with internal thread for inside wall
- Anti-twist wall rosette with internal thread for outside wall
- Fastening material

Technical data

- Material: Brass, conform to German drinking water regulations
- Surface: Matt chrome
- hole diameter: 38 mm
- Connection: DN 15 G 1/2 AG
- Outlet: Hose screw connection Ø 14.5 mm (DN 20 G 3/4 AG)
- Safety device, conforms to EN 1717: HD
- Certificates: P-IX 19319/II, DVGW, Belgaqua
- Noise class: II

Delivery data

- Weight: 1,92 kg/Piece
- Packing unit: 8

Recommended associated articles

For protection against unauthorised release of water

COMFORT handle SECUR

Article no: 48 006 06 99