

Article number: 02 185 06 99

Exposed shower tap MODUS MD-T

Mixed water, ThermoProtect thermostat

Manual open/closed actuation.

Scope of delivery




- Open/closed exposed shower tap
 - Operating button open/close
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - IsoBody housing
 - Open/closed ceramic cartridge
- 2 backflow preventers (EN 1717: EB-type)
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Max. operating temperature: 65 °C (for thermal disinfection 80 °C max. 10 min./day)
- Max. Outlet temperature: 38 - 43 °C adjustable
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Connection: 2x DN 15 G 1/2 AG
- Outlet: DN 15 G 1/2 AG (bottom)
- Certificates: PA-IX 38399/IS, DVGW, Belgaqua
- Noise class: I
- Flow class: S

Delivery data

- Weight: 2,10 kg/Piece
- Packing unit: 1



Recommended associated articles

Shower set 900	Article no: 29 207 06 99	or
Shower set 680	Article no: 29 208 06 99	or
	Article no: 29 239 00 99	or
	Article no: 29 240 00 99	or

Hint

- Special tool 29 242 00 99 required for thermostat maintenance work.
- Noise class I only in conjunction with hand shower with noise class I and flow class up to S.