

Article number: 09 416 06 99

Angle valve thermostat set

Flexible design

Thermostatic anti-scalding protection fitting incl. flexible connecting set for installation on angle valves with G 3/8 AG outlet. Setting of max. draw-off temperature, concealed under cover cap, only possible with tool.

Scope of delivery

Angle valve thermostat (09 414 06 99)

- Angle valve thermostat
 - ThermoProtect thermostat, conform to EN 1111, anti-scalding protection if cold water supply fails
 - 2 backflow preventers (EN 1717: EB-type)
 - 2 pre-filters

Connecting set for angle valve thermostat (04 116 06 99)

- T-piece with movable union nut G 3/8 IG
- Flexible Clean-Flex S hose with union nuts.

Technical data

Angle valve thermostat (09 414 06 99)

- Material: Cover cap Plastic; Housing Brass, conform to German drinking water regulations
- Thermal disinfection: possible, after releasing the temperature lock
- Flow at 3 bar: 13 l/min
- Max. operating temperature: 63 °C (70 °C for a short time for thermal disinfection)
- Max. Outlet temperature: 33 - 50 °C adjustable (38 °C $\pm$ 2 K)
- Surface: Chrome
- Connection: G 3/8 IG, G 3/8 AG
- Outlet: G 3/8 AG
- Certificates: P-IX 29876/I, DIN-DVGW, ACS, Belgaqua, WRAS
- Noise class: I, at 100% flow

Connecting set for angle valve thermostat (04 116 06 99)

- Surface: Chrome
- Connection: G 3/8 IG

5. Certificates: P-IX 29876/I, DIN-DVGW, ACS, Belgaqua, WRAS

6. Noise class: I, at 100% flow

Delivery data

- Weight: 0,83 kg/Set
- Packing unit: 1



Recommended associated articles

Angle valve COMFORT PT	Article no: 04 992 06 99	or
Sampling pipe for sampling valves	Article no: 03 835 06 99	or

Mounting instructions

- Suitable for angle valve installation with a max. centre-to-centre distance of 340 mm.