

Article number: 10 868 06 99

Fitting connection set COMFORT

For connecting single-hole taps and an additional appliance connection to the cold/hot water connection.

Scope of delivery

Combination angle valve COMFORT (03 549 06 99)

- Combination angle valve
 - 2 COMFORT handles
 - Backflow preventer (EN 1717: EB-type) in appliance connection outlet
 - Anti-vacuum device (EN 1717: HB-type) in appliance connection outlet
 - ASAG easy (Self-sealing connection thread)
 - Grease chamber head part
 - Long push rod
- Hose screw connection
- High-tensile brass cone compression connection with length compensation
- Push rosette Ø 54 mm

Angle valve with regulating function COMFORT (04 917 06 99)

- Angle valve
 - COMFORT handle
 - ASAG easy (Self-sealing connection thread)
 - Long push rod
- High-tensile brass cone compression connection with length compensation
- Push rosette Ø 54 mm

Technical data

Combination angle valve COMFORT (03 549 06 99)

- Material: Brass, conform to German drinking water regulations
- Surface: Chrome
- Connection: DN 15 G 1/2 AG with ASAG easy
- Outlet: Ø 10 mm (DN 10 G 3/8 AG), Hose screw connection Ø 14.5 mm (DN 20 G 3/4 AG)
- Safety device, conforms to EN 1717: HD
- Certificates: PA-IX 026/IIA, DVGW, ACS, Belgaqua
- Noise class: II, at 100% flow
- Flow class: A

Angle valve with regulating function COMFORT (04 917 06 99)

- Material: Brass, conform to German drinking water regulations
- Surface: Chrome
- Connection: DN 15 G 1/2 AG with ASAG easy
- Outlet: Ø 10 mm (DN 10 G 3/8 AG)
- Certificates: P-IX 212/IA, DIN-DVGW, ACS, NF, WRAS applied
- Noise class: I
- Flow class: A

Delivery data

- Weight: 0,62 kg/Set
- Packing unit: 1



