

Article number: 01 918 06 99

## Concealed shower LINUS D-C-T Mixed water, ThermoProtect thermostat

For WBD-E-T concealed masterbox. Triggering via CVD-Touch electronics with automatic closing. Optional battery or mains operation. Suitable for networking with the SCHELL SWS water management system. Configurable via SCHELL Single Control SSC.



### Scope of delivery

- Front panel
  - CVD-Touch electronics, programmable, IP65 protection against low-pressure water jets
  - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
- Installation frame
- Fastening material

### Technical data

- Setting options via SWS SSC
  - Actuation force (soft/medium/hard)
  - Manual programming (off/on)
  - Max. flow time (1-950 s)
  - Stagnation flush (off/1-1000 s, every 1-250 h after last flush/every 1-250 h)
  - Actuation timeout (off/1-255 s, timeout 1-2000 min)
- Setting options via manual programming
  - Max. flow time (4-120 s, 10 program stages)
  - Stagnation flush (off/20 s, every 24 h)
- Material: Actuation Brass, Front panel Brass
- Surface: Actuation Chrome, Front panel Chrome
- Dimensions front plate: W 173 mm x h 281 mm x d 11.5 mm
- Protection class: IP65 (CVD touch electronics)



### Delivery data

- Weight: 1,92 kg/Piece
- Packing unit: 1

### Necessary associated articles

Concealed Masterbox WBD-E-T	Article no: 01 802 00 99
Universal 6 V battery compartment	Article no: 01 557 00 99 or
Concealed power supply unit 9 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 315 00 99 or
Top-hat rail transformer 9 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 582 00 99 or
Electrical junction box 9 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 583 00 99 or

### Recommended associated articles

Universal connection cable 5 m	Article no: 01 570 00 99 or
Universal connection cable 10 m	Article no: 01 571 00 99 or
CVD-protection filter	Article no: 00 906 00 99
Handle for thermostat EasyGrip	Article no: 29 192 06 99

Shower head COMFORT Flex	Article no: 01 821 06 99 or
Low aerosol shower head	Article no: 01 814 06 99 or
SWS Server	Article no: 00 500 00 99
SWS Bus extender cable BE-K	Article no: 00 501 00 99 and/or
SWS Bus extender wireless BE-F	Article no: 00 502 00 99 and/or
SSC Bluetooth® module	Article no: 00 916 00 99
Wall connection elbow PURIS	Article no: 06 469 06 99 or
Wall connection elbow	Article no: 06 463 06 99 or
<u>For thermal disinfection with SWS</u>	
Solenoid valve thermal disinfection SWS	Article no: 01 874 00 99
<u>For manual thermal disinfection</u>	
Solenoid valve thermal disinfection	Article no: 01 875 00 99
Thermal disinfection key switch	Article no: 01 538 00 99
Concealed power supply unit 12 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 566 00 99 or
Mains adapter VDC, 100-240 VAC, 50-60 Hz	Article no: 01 490 00 99 or
Electrical junction box 12 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 537 00 99 or
<u>Where masterbox installation is too deep</u>	
Extension set D-E-T 25 mm	Article no: 01 860 06 99 or
Extension set D-E-T 50 mm	Article no: 01 865 06 99 or