

Article number: 01 827 00 99

Concealed Masterbox WBD-SC-V Pre-mixed water



For LINUS D-SC-V concealed shower fittings. Manual actuation with automatic closing. With sealed housing bushings and internal isolating valve.

Scope of delivery


- Masterbox
 - Concealed shower tap with isolating valve
 - Pre-filter
 - Roughing-in housing
 - Backflow preventer (EN 1717: EB-type)
 - Self-closing cartridge SC II
- Flushing nozzle
- Flush-mounted cap

Technical data

- Running time: 5 - 30 s adjustable
- Flow at 3 bar: 10 l/min
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Installation depth: 80 - 104 mm
- Connection: G 1/2 IG
- Outlet: G 1/2 IG
- Material: Housing Plastic, Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Dimensions: W 138 mm x h 149 mm x d 120 mm
- Certificates: P-IX 19960/IB, DIN-DVGW, Belgauqa
- Noise class: I
- Flow class: B

Delivery data

- Weight: 1,70 kg/Piece
- Packing unit: 1



Necessary associated articles

Concealed shower LINUS D-SC-V	Article no: 01 833 06 99	or
Concealed shower LINUS D-SC-V	Article no: 01 833 28 99	or
<u>For building sealing according to DIN 18534</u>		
Expansion sleeve	Article no: 00 919 00 99	

Recommended associated articles

Shower module MONTUS	Article no: 03 091 00 99
----------------------	--------------------------