

Article number: 00 804 08 99

## Shower panel LINUS DP-SC-V

### Pre-mixed water

Made from a strong extruded aluminium profile with a high-quality, anodised finish. Manual actuation with automatic closing. Pivoting front panel for easy installation and servicing. Suitable for connections from rear or for exposed connections from above.

#### Scope of delivery

- Self-closing exposed shower panel
  - SC self-closing button
  - Self-closing cartridge SC II
- Shower head COMFORT Flex, adjustable angle of inclination 12 - 32°, vandal-resistant, with soft jet and anti-limescale knob
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

#### Technical data

- Running time: 5 - 30 s adjustable (20 s )
- Flow: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C temporarily
- Connection: DN 15 G 1/2 AG
- Material: Actuation Brass, Shower head Brass, conform to German drinking water regulations, Housing Aluminium, Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Surface: Actuation Chrome, Shower head Chrome, Housing Brush anodised aluminium
- Dimensions: W 226 mm x h 1200 mm x d 115 mm
- Certificates: Belgaqua

#### Delivery data

- Weight: 12,00 kg/Piece
- Packing unit: 1

#### Recommended associated articles

Soap tray shower panel LINUS  
 Pipe set shower panel connection 500 mm  
 Pipe set shower panel connection 1000 mm  
 Connection cover shower panel LINUS 150 - 450 mm  
 Connection cover shower panel LINUS 150 - 950 mm  
 Sampling valve COMFORT Flex

Article no: 00 809 08 99  
 Article no: 08 481 06 99 or  
 Article no: 08 482 06 99 or  
 Article no: 00 839 08 99 or  
 Article no: 00 840 08 99 or  
 Article no: 01 823 00 99

