

Article number: 00 824 08 99

Shower panel LINUS DP-SC-T

Mixed water, ThermoProtect thermostat

Suitable for connections from rear or for exposed connections from above.

Scope of delivery



- Self-closing exposed shower panel
 - 2 pre-filters
 - SC self-closing button
 - 2 backflow preventers (EN 1717: EB-type)
 - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
 - ThermoProtect thermostat, conform to EN 1111, anti-scalding protection if cold water supply fails
 - Self-closing cartridge SC II
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

Technical data

- Running time: 5 - 30 s adjustable (20 s)
- Flow: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C temporarily
- Connection: 2x DN 15 G 1/2 AG
- Material: Actuation Brass, Shower head Brass, conform to German drinking water regulations, Housing Aluminium, Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Surface: Actuation Chrome, Shower head Chrome, Housing Brush anodised aluminium
- Dimensions: W 226 mm x h 1200 mm x d 115 mm
- Certificates: Belgaqua

Delivery data

- Weight: 15,50 kg/Piece
- Packing unit: 1



Recommended associated articles

Soap tray shower panel LINUS

Article no: 00 809 08 99

Handle for thermostat EasyGrip

Article no: 29 192 06 99

Sampling valve for shower heads

Article no: 01 817 00 99

For exposed connections from above

Pipe set shower panel connection 500 mm

Article no: 08 481 06 99 or

Pipe set shower panel connection 1000 mm

Article no: 08 482 06 99 or

Connection cover shower panel LINUS 150 - 450 mm

Article no: 00 839 08 99 or

Connection cover shower panel LINUS 150 - 950 mm

Article no: 00 840 08 99 or