

Article number: 00 827 08 99

Shower panel LINUS DP-SC-V

Pre-mixed water

Made from a strong extruded aluminium profile with a high-quality, anodised finish. Manual actuation with automatic closing. Pivoting front panel for easy installation and servicing. Suitable for connections from rear or for exposed connections from above.

Scope of delivery

- Self-closing exposed shower panel
 - SC self-closing button
 - Self-closing cartridge SC II
- Low aerosol shower head 20° ±6°, vandal-resistant
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

Technical data

- Running time: 5 - 30 s adjustable (20 s)
- S_Durchfluss: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C temporarily
- Connection: DN 15 G 1/2 AG
- Material: Actuation Brass, Shower head Brass, conform to German drinking water regulations, Housing Aluminium, Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Surface: Actuation Chrome, Shower head Chrome, Housing Brush anodised aluminium
- Dimensions: W 226 mm x h 1200 mm x d 115 mm
- Certificates: Belgaqua

Delivery data

- Weight: 15,00 kg/Piece
- Packing unit: 1

Recommended associated articles

Soap tray shower panel LINUS

Pipe set shower panel connection 500 mm

Pipe set shower panel connection 1000 mm

Connection cover shower panel LINUS 150 - 450 mm

Connection cover shower panel LINUS 150 - 950 mm

Sampling valve for shower heads

Article no: 00 809 08 99

Article no: 08 481 06 99 or

Article no: 08 482 06 99 or

Article no: 00 839 08 99 or

Article no: 00 840 08 99 or

Article no: 01 817 00 99

