

Article number: 00 828 08 99

## Shower panel LINUS DP-EH-M Mixed water

Made from a strong extruded aluminium profile with a high-quality, anodised finish. Manual single-lever actuation. Pivoting front panel for easy installation and servicing. Suitable for connections from rear or for exposed connections from above.

### Scope of delivery

- Single-lever exposed shower panel
  - 2 backflow preventers (EN 1717: EB-type)
  - Single-lever mixer
  - Single-lever mixing ceramic cartridge with hot water and flow restrictor
- Shower head COMFORT Flex, adjustable angle of inclination 12 - 32°, vandal-resistant, with soft jet and anti-limescale knob
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

### Technical data

- S\_Durchfluss: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C temporarily
- Connection: 2x DN 15 G 1/2 AG
- Material: Actuation Die-cast zinc, Housing Aluminium, Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Surface: Actuation Chrome, Shower head Chrome, Housing Brushed anodised aluminium
- Dimensions: W 226 mm x h 1200 mm x d 115 mm
- Certificates: Belgaqua

### Delivery data

- Weight: 13,90 kg/Piece
- Packing unit: 1

### Recommended associated articles

Soap tray shower panel LINUS

Pipe set shower panel connection 500 mm

Pipe set shower panel connection 1000 mm

Connection cover shower panel LINUS 150 - 450 mm

Connection cover shower panel LINUS 150 - 950 mm

Sampling valve COMFORT Flex

Article no: 00 809 08 99

Article no: 08 481 06 99 or

Article no: 08 482 06 99 or

Article no: 00 839 08 99 or

Article no: 00 840 08 99 or

Article no: 01 823 00 99

