

Article number: 00 841 28 99

Shower panel LINUS Inox DP-C-T Mixed water, ThermoProtect thermostat

Suitable for connections from rear or for exposed connections from above.

Scope of delivery

- Electronic self-closing exposed shower panel
 - 2 pre-filters
 - CVD-Touch electronics, programmable, IP65 protection against low-pressure water jets
 - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
 - 2 backflow preventers (EN 1717: EB-type)
 - 6 V solenoid valve
 - ThermoProtect thermostat, conform to EN 1111, anti-scalding protection if cold water supply fails
- Shower head COMFORT Flex, adjustable angle of inclination 12 - 32°, vandal-resistant, with soft jet and anti-limescale knob
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

Technical data

- Setting options via SWS SSC
 - Actuation force (soft/medium/hard)
 - Manual programming (off/on)
 - Max. flow time (1-950 s)
 - Stagnation flush (off/1-1000 s, every 1-250 h after last flush/every 1-250 h)
 - Actuation timeout (off/1-255 s, timeout 1-2000 min)
- Setting options via manual programming
 - Max. flow time (10-360 s in 10 program stages, factory setting 20 s)
 - Stagnation flush (off/20 s, every 24 h)
- S_Durchfluss: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C temporarily
- Connection: 2x DN 15 G 1/2 AG
- Material: Actuation Brass, Housing Stainless steel 1.4404, Piping Plastic, conform to German drinking water regulations, Waterpath Brass, conform to German drinking water regulations
- Surface: Actuation Chrome, Housing Brushed stainless steel
- Dimensions: W 240 mm x h 1200 mm x d 80 mm
- Certificates: Belgaqua

Delivery data

- Weight: 11,92 kg/Piece
- Packing unit: 1



Necessary associated articles

For operation with SWS

SWS Server

Article no: 00 500 00 99

SWS Bus extender cable BE-K

Article no: 00 501 00 99 and/or

SWS Bus extender wireless BE-F Article no: 00 502 00 99 and/or

SWS Bus mains adapter Article no: 00 505 00 99

For operation with BE-F wireless bus extender or without SWS

Concealed power supply unit 9 VDC, 100 - 240 VAC, Article no: 01 315 00 99 or
50 - 60 Hz

Top-hat rail transformer 9 VDC, 100 - 240 VAC, 50 - Article no: 01 582 00 99 or
60 Hz

Electrical junction box 9 VDC, 100 - 240 VAC, 50 - Article no: 01 583 00 99 or
60 Hz

Universal 6 V battery compartment Article no: 01 557 00 99 or

Together with mains adapter

Universal connection cable 5 m Article no: 01 570 00 99 or

Universal connection cable 10 m Article no: 01 571 00 99 or

Recommended associated articles

Soap tray shower panel LINUS inox Article no: 00 850 28 99

Pipe set shower panel connection 500 mm Article no: 08 481 06 99 or

Pipe set shower panel connection 1000 mm Article no: 08 482 06 99 or

Connection cover shower panel LINUS inox Article no: 00 849 28 99 or

Connection cover shower panel LINUS inox Article no: 00 851 28 99 or

Handle for thermostat EasyGrip Article no: 29 192 06 99

Sampling valve COMFORT Flex Article no: 01 823 00 99

Low aerosol shower head Article no: 01 814 06 99

Not together with SWS and SSC Bluetooth module

CVD-protection filter Article no: 00 906 00 99