

Article number: 00 844 28 99

Shower panel LINUS Inox DP-SC-T

Mixed water, ThermoProtect thermostat

Suitable for connections from rear or for exposed connections from above.

Scope of delivery

- Self-closing exposed shower panel
 - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
 - SC self-closing button
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - Self-closing cartridge SC II
- 2 backflow preventers (EN 1717: EB-type)
- 2 pre-filters
- Shower head COMFORT Flex, adjustable angle of inclination 12 - 32°, vandal-resistant, with soft jet and anti-limescale knob
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

Technical data

- Running time: 5 - 30 s adjustable (20 s)
- - Noise class: II, at 100% flow: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C temporarily
- Connection: 2x DN 15 G 1/2 AG
- Material: Actuation Brass; Housing Stainless steel 1.4404; Piping Plastic, conform to German drinking water regulations; Waterpath Brass, conform to German drinking water regulations
- Surface: Actuation Chrome; Housing Brushed stainless steel
- Dimensions: W 240 mm x h 1200 mm x d 80 mm
- Certificates: Belgauqua

Delivery data

- Weight: 12,00 kg/Piece
- Packing unit: 1

Recommended associated articles

Soap tray shower panel LINUS inox	Article no: 00 850 28 99	
Pipe set shower panel connection 500 mm	Article no: 08 481 06 99	or
Pipe set shower panel connection 1000 mm	Article no: 08 482 06 99	or
Connection cover shower panel LINUS inox	Article no: 00 849 28 99	or
Connection cover shower panel LINUS inox	Article no: 00 851 28 99	or
Handle for thermostat EasyGrip	Article no: 29 192 06 99	
Sampling valve COMFORT Flex	Article no: 01 823 00 99	
Low aerosol shower head	Article no: 01 814 06 99	

