

Article number: 00 846 28 99

Shower panel LINUS Inox DP-C-T-H Mixed water, ThermoProtect thermostat

Made from high-quality stainless steel (1.4404) material with a brushed finish. Integrated SCHELL shower fitting. Triggering via CVD-Touch electronics with automatic closing. Optional battery or mains operation. Suitable for networking with the SCHELL SWS water management system. Configurable via SCHELL Single Control SSC. Pivoting front panel for easy installation and servicing. Suitable for connections from rear or for exposed connections from above.

Scope of delivery


- Electronic self-closing exposed shower panel
 - 2 pre-filters
 - CVD-Touch electronics, programmable, IP65 protection against low-pressure water jets
 - 2 backflow preventers (EN 1717: EB-type)
 - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
 - 6 V solenoid valve
 - ThermoProtect thermostat, conform to EN 1111, anti-scalding protection if cold water supply fails
- Hand shower, 3-way adjustable and connection hose
- Shower bar
- Connection accessories with isolating valve(s)
- Fastening material for wall installation

Technical data

- Setting options via SWS SSC
 - Actuation force (soft/medium/hard)
 - Manual programming (off/on)
 - Max. flow time (1-950 s)
 - Stagnation flush (off/1-1000 s, every 1-250 h after last flush/every 1-250 h)
 - Actuation timeout (off/1-255 s, timeout 1-2000 min)
- Setting options via manual programming
 - Max. flow time (10-360 s in 10 program stages, factory setting 20 s)
 - Stagnation flush (off/20 s, every 24 h)
- Flow: max. 9 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C temporarily
- Connection: 2x DN 15 G 1/2 AG
- Material: Actuation Brass, Housing Stainless steel 1.4404, Piping Plastic, conform to German drinking water regulations, Waterpath Brass, conform to German drinking water regulations
- Surface: Actuation Chrome, Housing Brushed stainless steel
- Dimensions: W 240 mm x h 1200 mm x d 80 mm
- length shower hose: 1500 mm
- length shower bar: 678 mm
- Certificates: Belgaqua

Delivery data

- Weight: 12,26 kg/Piece
- Packing unit: 1



Necessary associated articles

For operation with SWS

SWS Server	Article no: 00 500 00 99
SWS Bus extender cable BE-K	Article no: 00 501 00 99 and/or
SWS Bus extender wireless BE-F	Article no: 00 502 00 99 and/or
SWS Bus mains adapter	Article no: 00 505 00 99

For operation with BE-F wireless bus extender or without SWS

Concealed power supply unit 9 VDC, 100 - 240 VAC, Article no: 01 315 00 99 or 50 - 60 Hz	
Top-hat rail transformer 9 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 582 00 99 or
Electrical junction box 9 VDC, 100 - 240 VAC, 50 - 60 Hz	Article no: 01 583 00 99 or
	Article no: 01 557 00 99 or

Together with mains adapter

Universal connection cable 5 m	Article no: 01 570 00 99 or
Universal connection cable 10 m	Article no: 01 571 00 99 or

Recommended associated articles

Soap tray shower panel LINUS inox	Article no: 00 850 28 99
Pipe set shower panel connection 500 mm	Article no: 08 481 06 99 or
Pipe set shower panel connection 1000 mm	Article no: 08 482 06 99 or
Connection cover shower panel LINUS inox	Article no: 00 849 28 99 or
Connection cover shower panel LINUS inox	Article no: 00 851 28 99 or
	Article no: 29 192 06 99
SSC Bluetooth® module	Article no: 00 916 00 99
Flow restrictor LEED	Article no: 29 239 00 99 or
Flow restrictor BREEAM	Article no: 29 240 00 99 or

Not together with SWS and SSC Bluetooth module

Article no: 00 906 00 99