

Article number: 00 833 28 99

Shower panel LINUS Trend DP-SC-T Mixed water, ThermoProtect thermostat

Made from strong stainless steel with a high-quality, brushed finish. Manual actuation with automatic closing. Single-person assembly for easy installation and servicing. Suitable for connections from rear or for exposed connections from above.

Scope of delivery

- Self-closing exposed shower panel
 - Self-closing cartridge SC
 - SC self-closing button
 - Operating button for thermostat with push sleeve, temperature setting unlockable/lockable at 38 °C
 - ThermoProtect thermostat, conform to EN 1111, anti-scalding protection if cold water supply fails
- COMFORT shower head 13°, vandal-resistant, with soft stream and anti-limescale burles
- Connection accessories with isolating valve(s), backflow preventer (EN 1717: EB-type) and pre-filter
- Fastening material for wall installation

Technical data

- Running time: 5 - 30 s adjustable
- Flow at 3 bar: 9 l/min
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C temporarily
- Connection: 2x DN 15 G 1/2 AG
- Material: Actuation Brass, Shower head Brass, conform to German drinking water regulations, Housing Stainless steel
- Surface: Actuation Chrome, Shower head Chrome, Housing Brushed stainless steel
- Dimensions: W 220 mm x h 1263 mm x d 70 mm
- Certificates: Belgaqua

Delivery data

- Weight: 8,90 kg/Piece
- Packing unit: 1

Recommended associated articles

Soap tray LINUS Trend

Article no: 00 836 28 99

Hint

- Discontinued article, as long as stocks last



