

Article number: 01 603 06 99

Exposed shower tap VITUS VD -EH-M / o Mixed water

Manual open/closed actuation. Shower connection at top.

Scope of delivery




- Single-lever exposed shower tap
 - Single-lever mixer
 - Single-lever mixing ceramic cartridge with hot water and flow restrictor
- 2 backflow preventers (EN 1717: EB-type)
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Outlet: DN 15 G 1/2 AG (top)
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Certificates: PA-IX 38242/IB, Belgaqua
- Noise class: I
- Flow class: B

Delivery data

- Weight: 3,95 kg/Piece
- Packing unit: 1



Recommended associated articles

Flow restrictor LEED	Article no: 23 775 00 99	
Flow restrictor BREEAM	Article no: 29 239 00 99	or
	Article no: 29 240 00 99	or
<u>For concealed shower head connection</u>		
	Article no: 25 667 06 99	or
	Article no: 25 668 06 99	or
Shower head COMFORT Flex	Article no: 01 821 06 99	or
	Article no: 01 814 06 99	or
<u>For exposed shower head connection</u>		
Exposed pipe set VITUS	Article no: 25 666 06 99	
Exposed shower head COMFORT	Article no: 01 846 06 99	