

Article number: 01 605 06 99

## Exposed shower tap VITUS VD -SC-T /o Mixed water, ThermoProtect thermostat

Manual actuation with automatic closing. Easy flow time adjustment. Shower connection at top.

### Scope of delivery




- Self-closing exposed shower tap
  - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
  - SC self-closing button
  - 2 backflow preventers (EN 1717: EB-type)
  - Valve for carrying out manual thermal disinfection (in accordance with DVGW worksheet W 551)
  - Self-closing cartridge SC II
- 2 S-connections and rosettes (depth-adjustable)

### Technical data

- Running time: 5 - 30 s adjustable
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Outlet: DN 15 G 1/2 AG (top)
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Certificates: PA-IX 28574/IB, DVGW, Belgaqua
- Noise class: I
- Flow class: B

### Delivery data

- Weight: 4,04 kg/Piece
- Packing unit: 1



### Recommended associated articles

S-connecting with isolating valve	Article no: 23 775 00 99	
Flow restrictor LEED	Article no: 29 239 00 99	or
Flow restrictor BREEAM	Article no: 29 240 00 99	or
<u>For concealed shower head connection</u>		
Outlet elbow VITUS DN 15	Article no: 25 667 06 99	or
Outlet elbow VITUS DN 15	Article no: 25 668 06 99	or
Shower head COMFORT Flex	Article no: 01 821 06 99	or
Low aerosol shower head	Article no: 01 814 06 99	or
<u>For exposed shower head connection</u>		
Exposed pipe set VITUS	Article no: 25 666 06 99	
Exposed shower head COMFORT	Article no: 01 846 06 99	