Article number: 01 609 06 99

Exposed shower tap VITUS VD -C-T / o Mixed water, ThermoProtect thermostat

Triggering via CVD-Touch electronics with automatic closing. Battery operation. Shower connection at top. Suitable for networking with the SCHELL SWS water management system. Configurable via SCHELL Single Control SSC.







Scope of delivery

- Electronic self-closing exposed shower tap
  - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
  - 6 V solenoid valve with pre-filter
  - CVD-Touch electronics, programmable, IP65 protection against low-pressure water jets
  - 2 backflow preventers (EN 1717: EB-type)
  - Valve for carrying out manual thermal disinfection (in accordance with DVGW worksheet W 551)
  - 6 V battery compartment (integrated)
- 4x AA alkaline battery 1.5 V
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Setting options via SWS SSC
  - Actuation force (soft/medium/hard)
  - Manual programming (off/on)
  - Max. flow time (1-950 s)
  - Stagnation flush (off/1-1000 s, every 1-250 h after last flush/every 1-250 h)
  - Actuation timeout (off/1-255 s, timeout 1-2000 min)
- Setting options via manual programming
  - Max. flow time (4-120 s, 10 program stages)
  - Stagnation flush (off/20 s, every 24 h)
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Outlet: DN 15 G 1/2 AG (top)
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Certificates: PA-IX 28574/IB, Belgaqua
- Noise class: I
- Flow class: B

Delivery data

- Weight: 4,31 kg/Piece
- Packing unit: 1

Recommended associated articles

S-connecting with isolating valve	Article no: 23 775 00 99	
Flow restrictor LEED	Article no: 29 239 00 99	or
Flow restrictor BREEAM	Article no: 29 240 00 99	or

For concealed shower head connection

SCHELL GmbH & Co. KG Armaturentechnologie · Raiffeisenstraße 31 · 57462 Olpe · Germany
Tel. +49 2761 892-0 · Fax +49 2761 892-199 · info@schell.eu · www.schell.eu

Outlet elbow VITUS DN 15	Article no: 25 668 06 99	or
Outlet elbow VITUS DN 15	Article no: 25 667 06 99	or
Shower head COMFORT Flex	Article no: 01 821 06 99	or
Low aerosol shower head	Article no: 01 814 06 99	or
For exposed shower head connection		
Exposed pipe set VITUS	Article no: 25 666 06 99	
Exposed shower head COMFORT	Article no: 01 846 06 99	
For networking with SWS water management system		
SWS Server	Article no: 00 500 00 99	
SWS Bus extender wireless BE-F VITUS	Article no: 00 507 00 99	
For parametrisation with Single Control SSC		
SSC Bluetooth® module VITUS	Article no: 00 917 00 99	