

Article number: 01 610 06 99

Exposed shower tap VITUS VD -SC-T /u Mixed water, ThermoProtect thermostat

Manual actuation with automatic closing. Easy flow time adjustment. Shower connection at bottom.

Scope of delivery




- Self-closing exposed shower tap
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - SC self-closing button
 - 2 backflow preventers (EN 1717: EB-type)
 - Self-closing cartridge SC II
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Running time: 5 - 30 s adjustable
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Outlet: DN 15 G 1/2 AG (bottom)
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Certificates: PA-IX 28574/IB, DVGW, Belgaqua
- Noise class: I
- Flow class: B

Delivery data

- Weight: 4,05 kg/Piece
- Packing unit: 1



Recommended associated articles

	Article no: 23 775 00 99	
Shower set 900	Article no: 29 207 06 99	or
Shower set 680	Article no: 29 208 06 99	or
Flow restrictor LEED	Article no: 29 239 00 99	or
Flow restrictor BREEAM	Article no: 29 240 00 99	or