

Article number: 01 197 00 99

Urinal control COMPACT LC

Plug + play plug connector, IP 54.



Scope of delivery

- E-module
- Solenoid valve with adapter
- Concealed transformer 100-240 VAC, 50-60 Hz
- Urinal siphon with LC sensor

Technical data

- Functions
 - Stagnation flush (every 24 hours after last flush)
 - Automatic stadium program (reduced flush volume with high usage frequency >2 users/5 min)
 - Acoustic signal (when battery charge is low)
 - Odour trap flush (when water level is low)
 - Automatic flush stop (in case of blocked drain pipe)
- Setting options via Reedkontakt (accessories)
 - Flush programs (1 l, 2 l, hybrid flush)
 - Interval flush 5x (each flush 2 min contact time)
 - Cleaning flush 10 s
 - Cleaning stop 180 s
 - Diagnostics program

Delivery data

- Weight: 0,63 kg/Piece
- Packing unit: 1

Necessary associated articles

Urinal inlet connection DN 15 backflow preventer	Article no: 03 112 00 99 or
Urinal inlet connection DN 15	Article no: 03 105 00 99 or
Urinal module MONTUS	Article no: 03 089 00 99 or
Urinal module MONTUS	Article no: 03 075 00 99 or
Concealed urinal flush valve COMPACT II	Article no: 01 193 00 99 or

Recommended associated articles

Sensor cable COMPACT LC	Article no: 01 524 00 99
<u>For program setting externally at the ceramics</u>	
COMPACT LC reed contact	Article no: 01 529 00 99