

Article number: 02 477 06 99

## Exposed urinal flush valve SCHELLOMAT Basic SV, DN 15

All-metal design with brass push button. Conform to DIN EN 12541.

### Scope of delivery


- Exposed urinal flush valve
  - Isolating valve
  - Self-closing cartridge with nozzle bore pre-filter
- Urinal internal connector
- Push rosette Ø 60 mm
- Flush pipe Ø 18 mm x 193 mm

### Technical data

- Flow pressure: 0.8 - 5.0 bar
- Max. Resting pressure: 8 bar
- Connection: DN 15 G 1/2 AG
- Outlet: Internal connector Ø 43 mm (flush pipe Ø 18 mm)
- Flush flow: max. 0.3 l/s
- Flush volume adjustable: 1.0 - 6.0 l
- Material: Housing Brass, Parts in contact with water Brass, conform to German drinking water regulations, Plastic
- Surface: Chrome
- Certificates: PA-IX 9892/II, DIN-DVGW
- Noise class: II, at 100% flow

### Delivery data

- Weight: 0,71 kg/Piece
- Packing unit: 1



### Recommended associated articles

Flush pipe Ø 18 mm cranked	Article no: 50 223 06 99	or
Urinal external connector	Article no: 27 820 06 99	
Urinal module MONTUS	Article no: 03 090 00 99	