

Article number: 01 947 00 99

## Concealed Masterbox WBW-E-V Cold water/pre-mixed water

For LINUS W-E-V concealed wash basin taps. Electronic actuation. With sealed housing bushings and internal isolating valve.

### Scope of delivery



- Masterbox
  - Pre-filter
  - Roughing-in housing
  - Backflow preventer (EN 1717: EB-type)
  - Mount for wall outlet
  - 6 V solenoid valve
  - Concealed wash basin tap with isolating valve
- Flushing nozzle
- Flush-mounted cap

### Technical data

- Flow at 3 bar: 15 l/min
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Installation depth: 100 - 124 mm
- Connection: G 1/2 IG
- Material: Housing Plastic, Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Dimensions: W 149 mm x h 138 mm x d 140 mm
- Certificates: P-IX 18008/IA, Belgaqua
- Noise class: I
- Flow class: A

### Delivery data

- Weight: 1,98 kg/Piece
- Packing unit: 1



### Necessary associated articles

Concealed wash basin tap LINUS W-E-V	Article no: 01 938 06 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 939 06 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 938 28 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 939 28 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 941 06 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 942 06 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 941 28 99	or
Concealed wash basin tap LINUS W-E-V	Article no: 01 942 28 99	or
<u>For building sealing according to DIN 18534</u>		
Expansion sleeve	Article no: 00 919 00 99	

### Recommended associated articles

Wash basin module MONTUS	Article no: 03 088 00 99
--------------------------	--------------------------