

Article number: 00 241 06 99

Exposed wash basin tap VITUS VW-E-T Mixed water, ThermoProtect thermostat

Infrared sensor-controlled. Battery operation. With integrated SWS BE-F VITUS wireless bus extender for networking with the SWS water management system.

Scope of delivery

- Infrared sensor exposed wash basin tap
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - 6 V solenoid valve with pre-filter
 - 2 backflow preventers (EN 1717: EB-type)
 - Solenoid valve 6 V for carrying out thermal disinfection with SWS (in accordance with DVGW worksheet W 551)
 - Infrared sensor electronics, programmable
 - SWS BE-F VITUS wireless bus extender
 - Pivoting outlet (lockable) with aerator
 - 6 V battery compartment (integrated)
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Setting options via SWS SSC
 - Programming via short range reflex (off/on)
 - Max. flow time (1-600 s)
 - Stagnation flush (off/5-600 s, every 1-240 h after last flush/every 1-240 h)
 - Continuous flush for thermal disinfection (off/15-600 s)
 - Duration of flow (off/15-600 s)
 - Energy saving mode (off/1-254 h after last flush)
 - Cleaning stop (off/60-360 s)
- Setting options via short range reflex
 - Max. flow time (4-240 s, 12 program stages)
 - Stagnation flush (off/30 s, every 24 h after last flush/every 24 h)
 - Cleaning stop (off/60 s)
- S_Durchfluss: max. 5 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Material: Outlet Brass, conform to German drinking water regulations, Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 330 mm
- Certificates: Belgaqua

Delivery data

- Weight: 5,45 kg/Piece
- Packing unit: 1



Necessary associated articles

SWS Server Article no: 00 500 00 99

Recommended associated articles

S-connecting with isolating valve	Article no: 23 775 00 99	
Wash basin outlet valve OPEN	Article no: 02 002 06 99	or
Wash basin outlet valve PUSH OPEN	Article no: 02 000 06 99	or

Hint

- Discontinued article, as long as stocks last