

Article number: 01 636 06 99

## Exposed wash basin tap VITUS VW-AH-M Mixed water

Manual open/cold/hot actuation with clinic arm lever.

### Scope of delivery


- Open/cold/hot exposed wash basin tap
  - Open /cold/warm ceramic cartridge with hot water restrictor
  - 2 backflow preventers (EN 1717: EB-type)
  - Low aerosol aerator (laminar jet)
  - Ergonomic clinic arm lever 153 mm
  - Pivoting outlet (lockable)
- 2 S-connections and rosettes (depth-adjustable)

### Technical data

- Flow: 7.5 - 9.0 l/min
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Material: Outlet Brass, conform to German drinking water regulations, Actuation Brass, Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 270 mm
- Certificates: PA-IX 38239/IO, Belgaqua
- Noise class: I
- Flow class: O

### Delivery data

- Weight: 5,06 kg/Piece
- Packing unit: 1



### Recommended associated articles

S-connecting with isolating valve	Article no: 23 775 00 99	
Wash basin outlet valve OPEN	Article no: 02 002 06 99	or
Wash basin outlet valve PUSH OPEN	Article no: 02 000 06 99	or