

Article number: 01 651 06 99

## Exposed wash basin tap VITUS VW-SC-M Mixed water

Manual actuation with automatic closing. Easy flow time adjustment.

### Scope of delivery

- Self-closing exposed wash basin tap
  - 2 backflow preventers (EN 1717: EB-type)
  - Self-closing cartridge SC II with hot water restrictor
  - SC-M self-closing button
  - Valve for carrying out manual thermal disinfection (in accordance with DVGW worksheet W 551)
  - Pivoting outlet (lockable) with aerator
- 2 S-connections and rosettes (depth-adjustable)

### Technical data

- Running time: 2 - 15 s adjustable (7 s )
- $S_{\text{Durchfluss}}$ : max. 5 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Material: Outlet Brass, conform to German drinking water regulations, Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 210 mm
- Certificates: PA-IX 38237/IO, Belgaqua
- Noise class: I
- Flow class: O

### Delivery data

- Weight: 4,59 kg/Piece
- Packing unit: 1



### Recommended associated articles

S-connecting with isolating valve	Article no: 23 775 00 99	
Wash basin outlet valve OPEN	Article no: 02 002 06 99	or
Wash basin outlet valve PUSH OPEN	Article no: 02 000 06 99	or