

Article number: 01 653 06 99

Exposed wash basin tap VITUS VW-EH-M Mixed water

Manual single-lever actuation.

Scope of delivery

- Single-lever exposed wash basin tap
 - Operating handle made from brass
 - Valve for carrying out manual thermal disinfection (in accordance with DVGW worksheet W 551)
 - Single-lever mixing ceramic cartridge with hot water and flow restrictor
 - 2 backflow preventers (EN 1717: EB-type)
 - Pivoting outlet (lockable) with flow regulator
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- - Noise class: II, at 100% flow: max. 5 I/min pressure independent
- Flow pressure: 1.0 5.0 barMax. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Material: Outlet Brass, conform to German drinking water regulations; Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 210 mm
 Certificates: PA-IX 38238/IO, Belgagua
- Noise class: IFlow class: O

Delivery data

- Weight: 4,79 kg/Piece
- Packing unit: 1

Recommended associated articles

S-connecting with isolating valve Article no: 23 775 00 99

Wash basin outlet valve OPEN Article no: 02 002 06 99 or

Wash basin outlet valve PUSH OPEN Article no: 02 000 06 99 or







