




Article number: 01 658 06 99

Exposed wash basin tap VITUS VW-SC-T Mixed water, ThermoProtect thermostat

Manual actuation with automatic closing. Easy flow time adjustment.



Scope of delivery

- Self-closing exposed wash basin tap
 - SC self-closing button
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - Valve for carrying out manual thermal disinfection (in accordance with DVGW worksheet W 551)
 - Self-closing cartridge SC II
 - 2 backflow preventers (EN 1717: EB-type)
 - Pivoting outlet (lockable) with flow regulator
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Running time: 2 - 15 s adjustable (7 s)
- - Noise class: II, at 100% flow: max. 5 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Material: Outlet Brass, conform to German drinking water regulations; Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 270 mm
- Certificates: PA-IX 38234/IO, Belgaqua
- Noise class: I
- Flow class: O

Delivery data

- Weight: 5,08 kg/Piece
- Packing unit: 1

Recommended associated articles

S-connecting with isolating valve

Article no: 23 775 00 99

Wash basin outlet valve OPEN

Article no: 02 002 06 99

or

Wash basin outlet valve PUSH OPEN

Article no: 02 000 06 99

or