Article number: 01 660 06 99

Exposed wash basin tap VITUS VW-open/close-T
Mixed water, ThermoProtect thermostat

Manual open/closed actuation.







Scope of delivery

- Open/closed exposed wash basin tap
  - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
  - 2 backflow preventers (EN 1717: EB-type)
  - Operating button open/close
  - Valve for carrying out manual thermal disinfection (in accordance with DVGW worksheet W 551)
  - Open/closed ceramic cartridge
  - Pivoting outlet (lockable) with aerator
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- flow: max. 5 l/min pressure independent
- Flow pressure: 1.0 - 5.0 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Material: Outlet Brass, conform to German drinking water regulations, Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 270 mm
- Certificates: PA-IX 38236/IO, Belgaqua
- Noise class: I
- Flow class: O

Delivery data

- Weight: 5,26 kg/Piece
- Packing unit: 1

Recommended associated articles

S-connecting with isolating valve	Article no: 23 775 00 99