

Article number: 01 692 06 99

Exposed wash basin tap VITUS VWopen/close-T Mixed water, ThermoProtect thermostat

Manual open/closed actuation.

Scope of delivery

- Open/closed exposed wash basin tap
 - Operating button open/close
 - ThermoProtect thermostat, conform to EN 1111, unlockable/lockable temperature lock at 38 °C, anti-scalding protection if cold water supply fails
 - Valve for carrying out manual thermal disinfection (in accordance with DVGW worksheet W 551)
 - Open/closed ceramic cartridge
 - 2 backflow preventers (EN 1717: EB-type)
 - Pivoting outlet (lockable) with flow regulator
- 2 S-connections and rosettes (depth-adjustable)

Technical data

- Flow: max. 5 l/min pressure independent
- Flow pressure: 1.0 5.0 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 2x DN 15 G 1/2 AG
- Material: Outlet Brass, conform to German drinking water regulations; Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Projection to centre of aerator: 330 mm
- Certificates: Belgaqua

Delivery data

- Weight: 5,38 kg/Piece
- Packing unit: 1

Recommended associated articles


S-connecting with isolating valve


Article no: 23 775 00 99

Hint

• Discontinued article, as long as stocks last







210 / 270 / 330