

Article number: 00 294 06 99

Electronic wash basin tap CELIS E² ND-M - low pressure mixed water

Contactless, sensor-controlled tap with innovative ToF technology. Insensitive against reflective materials such as mirrors, saftety vests, etc. With integrated Bluetooth® interface. Configurable via SCHELL app. Suitable for networking with the SCHELL SWS water management system. Battery operation. For open hot water storage tanks.

Scope of delivery

- Time-of-flight sensor single-hole tap
 - Temperature controller with hot water restrictor
 - Time-of-flight sensor electronics (ToF) with automatic adjustment of the sensor range
 - 6 V axial solenoid valve with pre-filter
 - Aerator
 - Connection cable, 240 mm, with 3-pin plug connector, protection class IP65
- 6 V battery compartment, protection class IP65
- 4x AA alkaline battery 1.5 V
- Pre-filter with flow restrictor
- 3 flexible Clean-Fix S connection hoses, G 3/8 IG x 380/500 mm
- Fastening material for wash basin installation

Technical data

- Parametrisation: Quick configuration via preset operating modes (save electricity / save water / comfort)
- Manual programming: Individual settings in expert mode (sensor range, sensor measuring interval, person detection, max. runtime, run-on time)
- Stagnation flush: Stagnation flush (off / at intervals / smart demand-based flush taking usage into account / at fixed times [day(s), time])
- Continuous flush for thermal disinfection: Continuous flush for thermal disinfection, triggering via app (3 10 min)
- Continuous flow: Continuous flow, triggering via app (15 600 s)
- Cleaning stop: Cleaning stop, triggering via app or proximity reflex (off / 60 360 s)
- - Noise class: II, at 100% flow: max. 5 I/min pressure independent
- Flow pressure: 1.0 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: 3x G 3/8 IGMaterial: Housing Brass
- Surface: Chrome
- Certificates: PA-IX 10333/IO
- Noise class: IFlow class: O

Delivery data

• Packing unit: 1

Recommended associated articles

Extension cable Article no: 51 010 00 99 or





Extension cable

Angle valve with regulating function COMFORT with

filter

Wash basin outlet valve OPEN
Wash basin outlet valve PUSH OPEN

Article no: 51 023 00 99 or Article no: 05 430 06 99

Article no: 02 002 06 99 or Article no: 02 000 06 99 or

Hint

• Available in IV. Quarter 2025.