

Article number: 02 171 06 99


## Electronic wash basin tap MODUS Trend E HD-M - high-pressure mixed water

Mains operation.



### Scope of delivery

- Infrared sensor single-hole tap
  - 6 V solenoid valve with pre-filter
  - 2 flexible connection hoses, G 3/8 IG x 450 mm, with backflow preventer (DIN EN 1717: EB-type) and pre-filter
  - Aerator
  - Connection cable, 200 mm, with 2-pin plug, protection class IP65
  - Temperature controller
  - Infrared sensor electronics, programmable
- Transformer plug 6 VDC, 100-240 VAC, 50-60 Hz
- Fastening material for wash basin installation



### Technical data

- Setting options via short range reflex
  - Sensor range area (approx. 2-17 cm)
  - Cleaning stop (off/120 s)
- S\_Durchfluss: max. 1 gpm  $\approx$  3,8 l/min
- Flow pressure: 0.5 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (temporarily, e.g. for thermal disinfection)
- Connection: 2x G 3/8 IG
- Material: Housing Brass, conform to German drinking water regulations
- Surface: Chrome
- Certificates: P-IX 29853/IO, WRAS applied
- Noise class: I
- Flow class: O

### Delivery data

- Weight: 1,71 kg/Piece
- Packing unit: 1

### Recommended associated articles

Angle valve with regulating function COMFORT with filter Article no: 05 430 06 99  
 Flow regulator set LEED 1.3 I Article no: 28 931 06 99