

Article number: 01 955 06 99

# Exposed wash basin tap MODUS E HD-K - high-pressure cold water/pre-mixed water



Infrared sensor-controlled. Battery operation.

## Scope of delivery

- Infrared sensor wall outlet tap
  - Aerator
  - Isolating valve
  - Infrared sensor electronics, programmable
  - 6 V solenoid valve
  - 6 V battery compartment (integrated)
- 4x AA alkaline battery 1.5 V
- Push rosette

## Technical data

- Setting options via short range reflex
  - Sensor range area (approx. 2-13 cm)
  - Stagnation flush (off/duration of flow 30 s, 24 h after last use)
  - Cleaning stop (off/120 s)
- Flow at 3 bar: 3 l/min
- Flow pressure: 0.5 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (for thermal disinfection 80 °C max. 10 min./day)
- Connection: G 1/2 AG
- Material: Housing DZR brass
- Surface: Chrome
- Projection to centre of aerator: 230 mm
- Certificates: dr, Watermark, WELS

## Delivery data

- Weight: 1,24 kg/Piece
- Packing unit: 1

---

## Recommended associated articles

Flow regulator set LEED 1.3 I	Article no: 28 931 06 99	
Wash basin outlet valve OPEN	Article no: 02 002 06 99	or
Wash basin outlet valve PUSH OPEN	Article no: 02 000 06 99	or