Article number: 02 173 06 99

Electronic wash basin tap MODUS E HD-K - high-pressure cold water/pre-mixed water

Infrared sensor-controlled. Mains operation.



Scope of delivery

- Infrared sensor single-hole tap
  - Infrared sensor electronics, programmable
  - 6 V solenoid valve with pre-filter
  - Flow regulator
  - Connection cable, 200 mm, with 2-pin plug, protection class IP65
  - Flexible connection hose, G 3/8 IG x 450 mm, with pre-filter
- Transformer plug 6 VDC, 100-240 VAC, 50-60 Hz
- Fastening material for wash basin installation

Technical data

- Setting options via short range reflex
  - Sensor range area (approx. 2-17 cm)
  - Stagnation flush (off/duration of flow 30 s, 24 h after last use)
  - Cleaning stop (off/120 s)
- Flow: max. 1 gpm ≈ 3,8 l/min
- Flow pressure: 0.5 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (temporarily, e.g. for thermal disinfection)
- Material: Brass, conform to German drinking water regulations
- Surface: Chrome
- Connection: G 3/8 IG
- Certificates: P-IX 29853/IO, WRAS applied
- Noise class: I
- Flow class: O

Delivery data

- Weight: 1,62 kg/Piece
- Packing unit: 1

Recommended associated articles

Angle valve with regulating function COMFORT with filter	Article no: 05 430 06 99
Flow regulator set LEED 1.3 l	Article no: 28 931 06 99 or

SCHELL GmbH & Co. KG Armaturentechnologie · Raiffeisenstraße 31 · 57462 Olpe · Germany
Tel. +49 2761 892-0 · Fax +49 2761 892-199 · info@schell.eu · www.schell.eu