

Article number: 02 173 06 99

## Electronic wash basin tap MODUS E HD-K - high-pressure cold water/pre-mixed water

Mains operation.

### Scope of delivery


- Infrared sensor single-hole tap
  - 6 V solenoid valve with pre-filter
  - Aerator
  - Connection cable, 200 mm, with 2-pin plug, protection class IP65
  - Flexible connection hose, G 3/8 IG x 450 mm, with pre-filter
  - Infrared sensor electronics, programmable
- Transformer plug 6 VDC, 100-240 VAC, 50-60 Hz
- Fastening material for wash basin installation

### Technical data

- Setting options via short range reflex
  - Sensor range area (approx. 2-17 cm)
  - Stagnation flush (off/duration of flow 30 s, 24 h after last use)
  - Cleaning stop (off/120 s)
- S\_Durchfluss: max. 1 gpm  $\approx$  3,8 l/min
- Flow pressure: 0.5 - 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (temporarily, e.g. for thermal disinfection)
- Connection: G 3/8 IG
- Material: Brass, conform to German drinking water regulations
- Surface: Chrome
- Certificates: P-IX 29853/IO, WRAS applied
- Noise class: I
- Flow class: O

### Delivery data

- Weight: 1,62 kg/Piece
- Packing unit: 1



### Recommended associated articles

|  |                             |
|--|-----------------------------|
| Angle valve with regulating function COMFORT with filter | Article no: 05 430 06 99    |
| Flow regulator set LEED 1.3 l                            | Article no: 28 931 06 99 or |
| Wash basin outlet valve OPEN                             | Article no: 02 002 06 99 or |
| Wash basin outlet valve PUSH OPEN                        | Article no: 02 000 06 99 or |