

Article number: 00 249 06 99

Electronic wash basin tap XERIS E² HD-K small - high-pressure cold water/premixed water

Contactless, sensor-controlled tap with innovative ToF technology. Insensitive against reflective materials such as mirrors, saftety vests, etc. With integrated Bluetooth® interface. Configurable via SCHELL app. Suitable for networking with the SCHELL SWS water management system. Excluding power supply. Intended for power supply via SCHELL water management system SWS or central power supply unit.

Scope of delivery

- Time-of-flight sensor single-hole tap
 - Time-of-flight sensor electronics (ToF) with automatic adjustment of the sensor range
 - 6 V axial solenoid valve with pre-filter
 - Recessed aerator (theft-protected)
 - Connection cable, 240 mm, with 3-pin plug connector, protection class IP65
- Flexible Clean-Fix S connection hose, G 3/8 IG x 410 mm, with integrated backflow preventer (EN 1717: EB-type) and pre-filter
- Fastening material for wash basin installation


Technical data

- Parametrisation: Quick configuration via preset operating modes (save electricity / save water / comfort)
- Manual programming: Individual settings in expert mode (sensor range, sensor measuring interval, person detection, max. runtime, run-on time)
- Stagnation flush: Stagnation flush (off / at intervals / smart demand-based flush taking usage into account / at fixed times [day(s), time])
- Continuous flush for thermal disinfection: Continuous flush for thermal disinfection, triggering via app (3 10 min)
- Continuous flow: Continuous flow, triggering via app (15 600 s)
- Cleaning stop: Cleaning stop, triggering via app or proximity reflex (off / 60 360 s)
- - Noise class: II, at 100% flow: max. 5 l/min pressure independent
- Flow pressure: 1.0 5.0 bar
- Max. Resting pressure: 8 bar
- Max. operating temperature: 70 °C (80 °C for thermal disinfection)
- Connection: G 3/8 IG
- Material: Housing Brass
- Surface: Chrome
- Certificates: PA-IX 10332/IO, DVGW applied
- Noise class: IFlow class: O

Delivery data

Weight: 1,50 kg/PiecePacking unit: 1







Necessary associated articles

SWS Server Article no: 00 500 00 99
SWS Bus mains adapter Article no: 00 505 00 99
SWS Bus extender cable BE-K Article no: 00 501 00 99

Recommended associated articles

Angle valve with regulating function COMFORT with Article no: 05 430 06 99

filter

Wash basin outlet valve OPEN Article no: 02 002 06 99 or Wash basin outlet valve PUSH OPEN Article no: 02 000 06 99 or

Optional power supply via collective mains adapter

Concealed power supply unit 9 VDC, 100 - 240 VAC, 50 Article no: 01 315 00 99 or

60 Hz

Top-hat rail transformer 9 VDC, 100 - 240 VAC, 50 - 60 Article no: 01 582 00 99 or

ΗZ

Electrical junction box 9 VDC, 100 - 240 VAC, 50 - 60 Hz Article no: 01 583 00 99 or

Hint

• Previous Electronic washbasin tap XERIS E 00 218 06 99 expected to be available until II. quarter 2025.