Article number: 01 137 00 99

Concealed WC flush valves COMPACT II ND

Low-noise concealed low-pressure flush valve. For combination with all SCHELL ND WC controls/operating panels. Conform to DIN EN 12541. Internal isolating valve.

Scope of delivery

- Masterbox
  - Concealed flush valve COMPACT II ND, with isolating valve and flush plug
  - Roughing-in housing
  - Pipe interrupter (DIN EN 12541)
- Flush-mounted cap
- Height-adjustable flush pipe with construction plug

Technical data

- Flow pressure: 0.8 - 2.5 bar
- Connection: DN 25 G 1 AG (right)
- Outlet: Flush pipe Ø 45 mm
- Flush flow: 1.4 l/s
- Material: Housing Plastic, Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Certificates: dr, Watermark, WELS

Delivery data

- Weight: 1,67 kg/Piece
- Packing unit: 1





Necessary associated articles

WC operating panel EDITION ND	Article no: 02 815 06 99	or
WC operating panel EDITION ND	Article no: 02 815 15 99	or
WC operating panel EDITION ND	Article no: 02 815 28 99	or
WC operating panel EDITION Eco ND	Article no: 02 814 06 99	or
WC operating panel EDITION Eco ND	Article no: 02 814 15 99	or
WC operating panel EDITION Eco ND	Article no: 02 814 28 99	or
WC operating panel EDITION Eco ND 100	Article no: 02 824 06 99	or