

Article number: 01 194 00 99

Concealed WC flush valves COMPACT II

Low-noise concealed flush valve. For combination with all SCHELL WC controls/operating panels. Conform to DIN EN 12541. Internal isolating valve.

Scope of delivery

- Masterbox
 - Concealed flush valve COMPACT II, with isolating valve and flush plug
 - Roughing-in housing
 - Pipe interrupter (DIN EN 12541)
- Flush-mounted cap
- Height-adjustable flush pipe with construction plug

Technical data

- Flow pressure: 1.2 - 5.0 bar
- Max. Resting pressure: 8 bar
- Connection: DN 20 G 3/4 AG (right)
- Outlet: Flush pipe \varnothing 45 mm
- Flush flow: 1.0 - 1.3 l/s
- Material: Housing Plastic, Waterpath Dezincification-resistant brass, conform to German drinking water regulations
- Certificates: PA-IX 18844/I, DIN-DVGW applied, Belgaqua
- Noise class: I, at 100% flow

Delivery data

- Weight: 1,63 kg/Piece
- Packing unit: 1

Necessary associated articles

WC control EDITION E Manual	Article no: 01 028 28 99	or
WC control EDITION E	Article no: 01 027 28 99	or
WC operating panel EDITION	Article no: 02 802 06 99	or
WC operating panel EDITION	Article no: 02 802 15 99	or
WC operating panel EDITION	Article no: 02 803 28 99	or
WC operating panel EDITION Eco	Article no: 02 804 06 99	or
WC operating panel EDITION Eco	Article no: 02 804 15 99	or
WC operating panel EDITION Eco	Article no: 02 805 28 99	or
WC operating panel EDITION Eco 100	Article no: 02 825 06 99	or

Recommended associated articles

WC cartridge EDITION Eco (LEED / BREEAM-compatible) Article no: 29 758 00 99

Mounting instructions

- For electronic triggering, provide power supply in accordance with the respective WC control.
- When used with the SCHELL SWS water management system, use a standard bus cable H(St)H2x2x0.8 (provided on site) for the SWS BE-K wired bus extender as required.
- Always use original SCHELL mains adapters and connection cables.
- Required supply line DN 25

