

Article number: 03 123 06 99

Contact-free infrared sensor flushing facility with button for manual actuation. Dual flush. Actuation from front. Vandal-resistant, zinc die-cast version.

### Scope of delivery


- Front panel with infrared sensor window and button for manual actuation
- Concealed transformer 12 VDC, 100-240 VAC, 50-60 Hz

### Technical data

- Stagnation flush: Stagnation flush (24 hours after last flush)
- Material: Front panel Die-cast zinc
- Surface: Front panel Chrome
- Dimensions front plate: W 240 mm x h 162 mm x d 15 mm

### Delivery data

- Weight: 1,44 kg/Piece
- Packing unit: 1



### Necessary associated articles

For MONTUS WC modules with concealed cisterns 8 cm

Article no: 03 125 00 99

For MONTUS WC modules with concealed cisterns 12 cm

Article no: 03 127 00 99

### In connection with

MONTUS WC modules with concealed cisterns 8 cm

WC module MONTUS Article no: 03 061 00 99 or

WC module MONTUS Article no: 03 059 00 99 or

MONTUS WC modules with concealed cisterns 12 cm

WC module MONTUS Flow Article no: 03 038 00 99 or

WC module MONTUS Flow H Article no: 03 037 00 99 or

WC module MONTUS Article no: 03 056 00 99 or

WC module MONTUS Article no: 03 057 00 99 or

WC module MONTUS Article no: 03 066 00 99 or

WC module MONTUS Article no: 03 058 00 99 or

Concealed WC cistern MONTUS Article no: 03 073 00 99 or